

```

PDEParabImpl := proc (n, m, k, a, b, g, e, f, alfa1, beta1, alfa2, beta2, gama1, gama2, phi)
  local h, n1, m1, u, i, j, alfa, beta, x, F, d1, d2, d3, p, q, r, s, pom, up, df;
  with(linalg);
  h := (b-a)/n;
  n1 := n + 1;
  m1 := m + 1;
  alfa := evalf(k/(h*h));
  beta := evalf(k/(2*h));
  df := D[3](f);
  x := Vector(n1, i → a + (i-1)*h);
  u := Matrix((m1, n1), 0);
  d1 := Vector(n-1, 0);
  d2 := Vector(n-1, 0);
  d3 := Vector(n-1, 0);
  F := Vector(n-1, 0);
  #profil u - 0 vrstva
  for i from 1 to n1 do
    u[1, i] := evalf(phi(x[i]));
  end do;
  #Výpo et diagonál v matici A a pravé strany, u(j+1)=F(j)+A*u(j)
  for j from 1 to m do
    for i from 1 to n-1 do
      d1[i] := -evalf(g(x[i+1], j*k) * alfa - e(x[i+1], j*k) * beta);
      d2[i] := evalf(1 + 2 * alfa * g(x[i+1], j*k) - k * df(x[i+1], j*k, u[j, i+1]));
      d3[i] := -evalf(g(x[i+1], j*k) * alfa + e(x[i+1], j*k) * beta);
      F[i] := evalf(u[j, i+1] - (k * df(x[i+1], j*k, u[j, i+1])) * u[j, i+1] + k
        * f(x[i+1], j*k, u[j, i+1]));
    end do;
    # Dosezení okrajových podmínek do první a poslední rovnice
    p := 1 / (alfa1 * 2 * h - 3 * beta1(j * k));
    r := beta1(j * k) * p;
    pom := d1[1] * r;
    d2[1] := d2[1] - 4 * pom;
    d3[1] := d3[1] + pom;
    F[1] := F[1] - 2 * h * gama1(j * k) * d1[1] * p;
    q := 1 / (alfa2 * 2 * h + 3 * beta2(j * k));
    s := beta2(j * k) * q;
    pom := d3[n-1] * s;
    d2[n-1] := d2[n-1] + 4 * pom;
    d1[n-1] := d1[n-1] - pom;
    F[n-1] := F[n-1] - 2 * h * gama2(j * k) * d3[n-1] * q;
    # Výpo et profilu u - j+1 vrstva, tj. pro t=j*k
    up := TriDiagonalSolve(n-1, d1, d2, d3, F);
    for i from 2 to n do
      u[j+1, i] := up[i-1];
    end do;
    # výpo et okrajových podmínek - j+1 vrstva, tj. pro t=j*k
    u[j+1, 1] := 2 * h * gama1(j * k) * p - r * (4 * u[j+1, 2] - u[j+1, 3]);
    u[j+1, n1] := 2 * h * gama2(j * k) * q + s * (4 * u[j+1, n] - u[j+1, n-1]);
  end do;
  RETURN(eval(u));
end proc;

```

► P íklad 1:

```
phi := x → sin( evalf( Pi · x ) ) :  
alfa1 := 1 :  
beta1 := t → 0 :  
alfa2 := 1 :  
beta2 := t → 0 :  
gama1 := t → 0 :  
gama2 := t → 0 :  
g := ( x, t ) → 1 :  
e := ( x, t ) → 0 :  
f := ( x, t, y ) → 0 :  
n := 10 :  
m := 80 :  
k := 0.005 :  
h :=  $\frac{1.0}{n}$  ;  
T := k · m ;
```

0.1000000000

0.400

(1.1)


```
vys := PDEParabImpl( n, m, k, 0.0, 1.0, g, e, f, alfa1, beta1, alfa2, beta2, gama1, gama2, phi );
```

81 x 11 Matrix
Data Type: anything
Storage: rectangular
Order: Fortran_order

(1.2)

```
data := [ seq( [ seq( [ 0 + ( i - 1 ) · h, vys[ j, i ], i = 1 .. n + 1 ], j = 1 .. m + 1 ) ] :  
with( plots ) :
```

```
display( seq( listplot( data[ i ], i = 1 .. m ) );
```



```

a := subs(1 .. m + 1 = 0 .. T, 1 .. n + 1 = 0 .. 1, matrixplot(vys[1 .. m + 1, 1 .. n + 1], labels = [t,
x, u])) :
display(a, view = [0 .. T, 0 .. 1, 0 .. 1]);

```

